


# LL3-TX01

LL3

FIBERS

**SICK**  
Sensor Intelligence.



### Ordering information

Type	Part no.
LL3-TX01	5324173

Other models and accessories → [www.sick.com/LL3](http://www.sick.com/LL3)



### Detailed technical data

#### Features

<b>Device type</b>	Fibers
<b>Detection principle</b>	Through-beam system (consisting of a sender and a receiver)
<b>For fiber-optic sensor</b>	GLL170(T), WLL180T, WLL24 Ex
<b>Fiber length</b>	20,000 mm
<b>Fiber material</b>	Polymethylmethacrylat (PMMA)
<b>Jacket material</b>	Polyethylen (PE)
<b>Fiber head material</b>	Stainless steel
<b>Outer diameter, fiber-optic cable connection</b>	2.2 mm
<b>Fiber-optic cable cuttable</b>	✓
<b>Thread diameter (housing)</b>	M12
<b>Fiber-optic head design</b>	Threaded sleeve
<b>Fiber arrangement</b>	Monofiber
<b>Core structure</b>	Ø 1.5 mm Monofiber
<b>Bend radius, fibre-optic cable</b>	25 mm
<b>Angle of dispersion &lt; 60°</b>	Yes
<b>Compatibility with infrared light (1,450 nm)</b>	No
<b>Ambient operating temperature</b>	-40 °C ... +60 °C
<b>Highly flexible/elastic fibers (bend radius 1-4 mm)</b>	No
<b>Adapter end sleeves required</b>	No
<b>Angle of dispersion</b>	13.12°
<b>Integrated lens</b>	Yes
<b>Minimal object diameter</b>	0.5 mm <sup>1)</sup>
<b>Included with delivery</b>	Mounting, 4 x M12 hexagon nut, FC fiber cutter (5304141), protective cladding for fiber head
<b>Compatibility tip adapters</b>	No

<sup>1)</sup> Minimum detectable object was determined at optimum measuring distance and optimum setting.

#### Mechanics/electronics

<b>Bend radius, fibre-optic cable</b>	25 mm
<b>Ambient operating temperature</b>	-40 °C ... +60 °C

Classifications

<b>ECl@ss 5.0</b>	27270905
<b>ECl@ss 5.1.4</b>	27270905
<b>ECl@ss 6.0</b>	27270905
<b>ECl@ss 6.2</b>	27270905
<b>ECl@ss 7.0</b>	27270905
<b>ECl@ss 8.0</b>	27270905
<b>ECl@ss 8.1</b>	27270905
<b>ECl@ss 9.0</b>	27270905
<b>ECl@ss 10.0</b>	27270905
<b>ECl@ss 11.0</b>	27270905
<b>ETIM 5.0</b>	EC002651
<b>ETIM 6.0</b>	EC002651
<b>ETIM 7.0</b>	EC002651
<b>UNSPSC 16.0901</b>	39121528

Sensing ranges with WLL180T

<b>Operating mode 16 µs</b>	1,800 mm
<b>Operating mode 70 µs</b>	7,000 mm
<b>Operating mode 250 µs</b>	12,000 mm
<b>Operating mode 2 ms</b>	25,000 mm
<b>Operating mode 8 ms</b>	38,000 mm

Sensing ranges with GLL170


<b>Operating mode 250 µs</b>	2,700 mm
------------------------------	----------

Sensing ranges with GLL170T

<b>Operating mode 50 µs</b>	6,890 mm
<b>Operating mode 250 µs</b>	10,810 mm

Dimensional drawing (Dimensions in mm (inch))

LL3-TX01



All dimensions in mm

## SICK AT A GLANCE

SICK is one of the leading manufacturers of intelligent sensors and sensor solutions for industrial applications. A unique range of products and services creates the perfect basis for controlling processes securely and efficiently, protecting individuals from accidents and preventing damage to the environment.

We have extensive experience in a wide range of industries and understand their processes and requirements. With intelligent sensors, we can deliver exactly what our customers need. In application centers in Europe, Asia and North America, system solutions are tested and optimized in accordance with customer specifications. All this makes us a reliable supplier and development partner.

Comprehensive services complete our offering: SICK LifeTime Services provide support throughout the machine life cycle and ensure safety and productivity.

For us, that is “Sensor Intelligence.”

## WORLDWIDE PRESENCE:

Contacts and other locations –[www.sick.com](http://www.sick.com)