




YF8U14-150VA3XLEAX

SICK
Sensor Intelligence.



Ordering information

Type	Part no.
YF8U14-150VA3XLEAX	2095899

Other models and accessories → www.sick.com/



Detailed technical data

Technical specifications


Accessory group	Plug connectors and cables
Accessory family	Connecting cables
Connection type head A	Female connector, M8, 4-pin, straight, A-coded
Connection type head B	Flying leads
Locking plug connector	Screw connection
Connector material	TPU
Connector color	Black
Locking nut material	Zinc die-cast, nickel-plated
Seal material	FKM
Tightening torque	0.4 Nm
Width across flats	9
Cable	15 m, 4-wire, PVC
Jacket material	PVC
Jacket color	Gray
Cable diameter	4.8 mm
Conductor cross-section	0.25 mm ²
Shielding	Unshielded
Bending radius	
Flexible use	> 10 x cable diameter
Stationary position	> 5 x cable diameter
Nominal voltage, cable	300 V AC
Test voltage, cable	2,000 V AC
Reference voltage	
	50 V AC
	60 V DC
Rated impulse voltage	1.5 kV
Current loading	4 A
Signal type	Sensor/actuator cable

Application	Zones with chemicals						
Authorizations	UL						
UL File No.	E335179						
Enclosure rating	IP65 / IP66K / IP67						
Ambient operating temperature	<table border="0"> <tr> <td style="padding-left: 20px;">Flexible use</td> <td>-5 °C ... +80 °C</td> </tr> <tr> <td style="padding-left: 20px;">Stationary position</td> <td>-30 °C ... +80 °C</td> </tr> <tr> <td style="padding-left: 20px;">Head</td> <td>-25 °C ... +85 °C</td> </tr> </table>	Flexible use	-5 °C ... +80 °C	Stationary position	-30 °C ... +80 °C	Head	-25 °C ... +85 °C
Flexible use	-5 °C ... +80 °C						
Stationary position	-30 °C ... +80 °C						
Head	-25 °C ... +85 °C						
Contamination rating	3						
Insulation resistance	100 MΩ						
Overvoltage category	III						
Specific insulation resistance	30 mΩ						
Thermal resistance, piping	Flame retardant according to UL 1581 VW1 / CSA FT1						

Classifications

ECI@ss 5.0	19030312
ECI@ss 5.1.4	19030312
ECI@ss 6.0	27060304
ECI@ss 6.2	27060304
ECI@ss 7.0	27060304
ECI@ss 8.0	27060304
ECI@ss 8.1	27060304
ECI@ss 9.0	27060304
ECI@ss 10.0	27060304
ECI@ss 11.0	27060304
ECI@ss 12.0	27060304
ETIM 5.0	EC000830
ETIM 6.0	EC000830
ETIM 7.0	EC003249
ETIM 8.0	EC003249
UNSPSC 16.0901	26121604

Dimensional drawing (Dimensions in mm (inch))



SICK AT A GLANCE

SICK is one of the leading manufacturers of intelligent sensors and sensor solutions for industrial applications. A unique range of products and services creates the perfect basis for controlling processes securely and efficiently, protecting individuals from accidents and preventing damage to the environment.

We have extensive experience in a wide range of industries and understand their processes and requirements. With intelligent sensors, we can deliver exactly what our customers need. In application centers in Europe, Asia and North America, system solutions are tested and optimized in accordance with customer specifications. All this makes us a reliable supplier and development partner.

Comprehensive services complete our offering: SICK LifeTime Services provide support throughout the machine life cycle and ensure safety and productivity.

For us, that is “Sensor Intelligence.”

WORLDWIDE PRESENCE:

Contacts and other locations –www.sick.com