



WFE-030040B321

WFE

FORK SENSORS

SICK
Sensor Intelligence.



Ordering information

Type	Part no.
WFE-030040B321	1106551

Other models and accessories → www.sick.com/WFE

Illustration may differ



Detailed technical data

Features

Dimensions (W x H x D)	10 mm x 59.3 mm x 60.5 mm
Fork width	30 mm
Fork depth	40 mm
Minimum detectable object (MDO)	0.5 mm
Light source	LED, red
Adjustment	No adjustment possibility

Mechanics/electronics

Supply voltage	10 V DC ... 30 V DC
Ripple	< 10 %
Current consumption	< 30 mA ¹⁾
Switching frequency	5 kHz
Response time	100 µs
Stability of response time	± 20 µs
Switching output	Push-pull: PNP/NPN
Switching output (voltage)	Push-pull: PNP/NPN High = U _V - < 2 V/Low: ≤ 2 V
Switching mode	Dark switching
Switching output hysteresis	< 0.1 mm
Output current I_{max.}	100 mA
Initialization time	100 ms
Connection type	Connector M8, 3-pin
Protection class	III
Circuit protection	U _V connections, reverse polarity protected

¹⁾ Without load.

	Output Q short-circuit protected Interference pulse suppression
Enclosure rating	IP67
Weight	Approx. 70 g
Housing material	Plastic, ABS Coated carbon steel (frame)
Indication	LED indicator green: power on LED indicator, yellow: Status switching output Q

¹⁾ Without load.

Ambient data

Ambient operating temperature	-20 °C ... +60 °C
Ambient temperature, storage	-40 °C ... +75 °C
Ambient light immunity	Sunlight: ≤ 10,000 lx
Shock load	According to IEC 60068-2-27 (30 g/11 ms)
UL File No.	NRKH.E348498 & NRKH7.E348498

Classifications


eCl@ss 5.0	27270909
eCl@ss 5.1.4	27270909
eCl@ss 6.0	27270909
eCl@ss 6.2	27270909
eCl@ss 7.0	27270909
eCl@ss 8.0	27270909
eCl@ss 8.1	27270909
eCl@ss 9.0	27270909
eCl@ss 10.0	27270909
eCl@ss 11.0	27270909
eCl@ss 12.0	27270909
ETIM 5.0	EC002720
ETIM 6.0	EC002720
ETIM 7.0	EC002720
ETIM 8.0	EC002720
UNSPSC 16.0901	39121528

Connection/pin assignment

Connection type	Connector M8, 3-pin
Pin assignment	
BN 1	+ (L+)
BU 3	- (M)
BK 4	Q

Dimensional drawing (Dimensions in mm (inch))

WFE-xxxxxxx3xx




- ① Optical axis
- ② Mounting hole, \varnothing 4.3 mm
- ③ Only WFE-050/-080/-120/-180

Type	A (fork width)	B (fork depth)	C	C1	C2	C3
WFE-030040xxxx	30 (1.18)	39 (1.54)	30 (1.18)	5 (0.2)	24.3 (0.96)	-
WFE-050060xxxx	50 (1.97)	57 (2.25)	40 (1.57)	5 (0.2)	34.3 (1.35)	8 (0.31)
WFE-080060xxxx	80 (3.15)	57 (2.24)	70 (2.76)	5 (0.2)	34.3 (1.35)	8 (0.31)
WFE-120120xxxx	120 (4.72)	121.5 (4.78)	100 (3.94)	15.5 (0.61)	33.8 (1.31)	10 (0.39)
WFE-180120xxxx	180 (7.09)	121.5 (4.78)	152 (5.98)	20.5 (0.81)	36.8 (1.45)	8 (0.31)

Adjustments


WFE-xxxxxxxx1



- ① Status indicator LED, yellow: Status switching output
- ② LED indicator green: power

Connection type




Male connector, 3-pin



See table: **Connection/pin assignment**

Recommended accessories

Other models and accessories → www.sick.com/WFE

	Brief description	Type	Part no.
Plug connectors and cables			
	Head A: female connector, M8, 3-pin, straight, A-coded Head B: Flying leads Cable: Sensor/actuator cable, PVC, unshielded, 5 m	YF8U13-050VA1XLEAX	2095884
	Head A: female connector, M8, 3-pin, straight Cable: unshielded	DOS-0803-G	7902077
	Head A: male connector, M8, 3-pin, straight Cable: unshielded	STE-0803-G	6037322

SICK AT A GLANCE

SICK is one of the leading manufacturers of intelligent sensors and sensor solutions for industrial applications. A unique range of products and services creates the perfect basis for controlling processes securely and efficiently, protecting individuals from accidents and preventing damage to the environment.

We have extensive experience in a wide range of industries and understand their processes and requirements. With intelligent sensors, we can deliver exactly what our customers need. In application centers in Europe, Asia and North America, system solutions are tested and optimized in accordance with customer specifications. All this makes us a reliable supplier and development partner.

Comprehensive services complete our offering: SICK LifeTime Services provide support throughout the machine life cycle and ensure safety and productivity.

For us, that is “Sensor Intelligence.”

WORLDWIDE PRESENCE:

Contacts and other locations –www.sick.com